


Miniature Housing Units

Silver Series


- Rustproof housings made with a special alloy
- Bearings are high carbon chromium bearing steel

UFL000 type*

TWO-BOLT FLANGE UNITS
With Eccentric Collar Locking




UFL000



KFL000 type*

TWO-BOLT FLANGE UNITS
With Set Screw Locking



KFL000

| Unit NO. | Dimensions (mm / in.) | | | | | | | | | | | | Bolt Size mm/in. | Bearing No. | Housing No. | Weight (kg) |
|----------|-------------------------|------------------|-----------------|---------------|---------------|---------------|---------------|-----------------|----------------|----------------|--------------|-----------------|---------------------|----------------|----------------|----------------|
| | d | a | e | i | g | l | S | b | Z | B ₁ | n | ds | | | | |
| UFL000 | 10 | 60.0 2-23/64 | 45.0 1-25/35 | 5.5 7/32 | 5.5 7/32 | 11.5 29/64 | 7.0 9/32 | 36.0 1-27/64 | 15.5 39/64 | 17.5 0.689 | 4.0 0.157 | 17.0 43/64 | M6 | U000 | FL000 | 0.06 |
| UFL001 | 12 | 63.0 2-31/64 | 48.0 1-57/64 | 5.5 7/32 | 5.5 7/32 | 11.5 29/64 | 7.0 9/32 | 38.0 1-1/2 | 16.0 5/8 | 17.5 0.689 | 4.0 0.157 | 19.0 3/4 | | U001 | FL001 | 0.07 |
| UFL002 | 15 | 67.0 2-41/64 | 53.0 2-3/32 | 6.5 1/4 | 6.5 1/4 | 13.0 33/64 | 7.0 9/32 | 42.0 1-21/32 | 18.6 47/64 | 18.5 0.728 | 4.5 0.177 | 22.0 55/64 | | U002 | FL002 | 0.10 |
| UFL003 | 17 | 71.0 2-51/64 | 56.0 2-13/64 | 7.0 9/32 | 7.0 9/32 | 14.0 35/64 | 7.0 9/32 | 46.0 1-13/16 | 19.5 49/64 | 20.5 0.807 | 5.0 0.197 | 25.0 31/32 | M6 | U003 | FL003 | 0.13 |
| UFL004 | 20 | 90.0 3-35/64 | 71.0 2-51/64 | 8.0 5/16 | 8.0 5/16 | 16.0 5/8 | 10.0 25/64 | 55.0 2-11/64 | 23.0 29/32 | 24.5 0.965 | 6.0 0.236 | 30.0 1-3/16 | M8 | U004 | FL04-5 | 0.20 |
| UFL005 | 25 | 95.0 3-47/64 | 75.0 2-61/64 | 8.0 5/16 | 8.0 5/16 | 16.0 5/8 | 10.0 25/64 | 60.0 2-3/8 | 24.5 31/32 | 25.5 1.000 | 6.5 0.256 | 36.0 1-27/64 | M8 | U005 | FL05-6 | 0.25 |
| UFL006 | 30 | 112.0 4-13/32 | 85.0 3-11/32 | 9.0 23/64 | 9.0 23/64 | 18.0 23/32 | 13.0 33/64 | 70.0 2-3/4 | 27.0 1-1/6 | 26.5 1.040 | 6.5 0.256 | 42.0 1-21/32 | M10 | U006 | FL06-7 | 0.35 |
| UFL007 | 35 | 122.0 4-51/64 | 95.0 3-3/4 | 10.0 25/64 | 10.0 25/64 | 20.0 25/32 | 13.0 33/64 | 80.0 3-5/32 | 32.5 1-9/32 | 29.5 1.161 | 7.0 0.276 | 48.0 1-57/64 | M10 | U007 | FL07-8 | 0.50 |

| Unit NO. | Dimensions (mm / in.) | | | | | | | | | | | | Bolt Size mm/in. | Bearing No. | Housing No. | Weight (kg) |
|----------|-------------------------|------------------|-----------------|--------------|--------------|---------------|---------------|-----------------|---------------|---------------|--------------|--|---------------------|----------------|----------------|----------------|
| | d | a | e | i | g | l | S | b | Z | B | n | | | | | |
| KFL000 | 10 | 60.0 2-23/64 | 45.0 1-25/35 | 5.5 7/32 | 5.5 7/32 | 11.5 29/64 | 7.0 9/32 | 36.0 1-27/64 | 15.5 39/64 | 14.0 0.551 | 4.0 0.157 | | M6 | K000 | FL000 | 0.06 |
| KFL001 | 12 | 63.0 2-31/64 | 48.0 1-57/64 | 5.5 7/32 | 5.5 7/32 | 11.5 29/64 | 7.0 9/32 | 38.0 1-1/2 | 16.0 5/8 | 14.5 0.571 | 4.0 0.157 | | | K001 | FL001 | 0.07 |
| KFL002 | 15 | 67.0 2-41/64 | 53.0 2-3/32 | 6.5 1/4 | 6.5 1/4 | 13.0 33/64 | 7.0 9/32 | 42.0 1-21/32 | 18.6 47/64 | 16.5 0.650 | 4.5 0.177 | | | K002 | FL002 | 0.10 |
| KFL003 | 17 | 71.0 2-51/64 | 56.0 2-13/64 | 7.0 9/32 | 7.0 9/32 | 14.0 35/64 | 7.0 9/32 | 46.0 1-13/16 | 19.5 49/64 | 17.5 0.689 | 5.0 0.197 | | M6 | K003 | FL003 | 0.13 |
| KFL004 | 20 | 90.0 3-35/64 | 71.0 2-51/64 | 8.0 5/16 | 8.0 5/16 | 16.0 5/8 | 10.0 25/64 | 55.0 2-11/64 | 23.0 29/32 | 21.0 0.827 | 6.0 0.236 | | M8 | K004 | FL04-5 | 0.20 |
| KFL005 | 25 | 95.0 3-47/64 | 75.0 2-61/64 | 8.0 5/16 | 8.0 5/16 | 16.0 5/8 | 10.0 25/64 | 60.0 2-3/8 | 24.5 31/32 | 22.5 0.886 | 6.5 0.256 | | M8 | K005 | FL05-6 | 0.25 |
| KFL006 | 30 | 112.0 4-13/32 | 85.0 3-11/32 | 9.0 23/64 | 9.0 23/64 | 18.0 23/32 | 13.0 33/64 | 70.0 2-3/4 | 27.0 1-1/6 | 24.5 0.965 | 6.5 0.256 | | M10 | K006 | FL06-7 | 0.35 |

Also available in Stainless Steel, ask for details