



SPHERICAL THRUST BEARINGS

Part Number	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
29318M	90	155	39	28500	91500	3.08
29320M	100	170	42	34500	116000	3.94
29322M	110	190	48	44500	150000	5.78
29324M	120	210	54	53500	177000	7.92
29326M	130	225	58	61500	210000	9.76
29328M	140	240	60	68500	236000	11.4
29330M	150	250	60	67500	239000	12
29332M	160	270	67	82000	286000	15.9
29334M	170	280	67	85500	305000	16.6
29336M	180	300	73	99500	306000	21.2
29338M	190	320	78	115000	425000	26
29340M	200	340	85	128000	460000	31.9
29412M	60	130	42	27000	76500	2.75
29413M	65	14	45	32500	92000	3.41
29414M	70	150	48	36500	98000	4.1
29415M	75	160	51	41500	114000	4.98
29416M	80	170	54	45000	124000	5.95
29417M	85	180	58	51000	145000	7.19
29418M	90	190	60	57000	162000	8.28
29420M	100	210	67	68000	190000	11.2
29422M	110	230	73	78000	234000	14.7
29424M	120	250	78	93400	300000	18.1
29426M	130	270	85	110000	317000	23.6
29428M	140	280	85	116000	341000	24.6
29430M	150	300	90	125000	388000	29.6
29432M	160	320	95	143000	437000	35.9
29434M	170	340	103	160000	481000	44
29436M	180	360	109	176000	550000	52.2
29438M	190	380	115	193000	401000	61.4
29440M	200	400	122	216000	682000	73