



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

SUFFIX 2RS = 2 RUBBER SEALS

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
2200	10	30	14	8000	1800	0.048
2200-2RS	10	30	14	8000	1800	0.052
2201	12	32	14	8400	1900	0.052
2201-2RS	12	32	14	8400	1900	0.056
2202	15	35	14	8600	2000	0.056
2202-2RS	15	35	14	8600	2000	0.059
2203	17	40	16	10400	2500	0.087
2203-2RS	17	40	16	10400	2500	0.095
2204	20	47	18	16400	4100	0.130
2204-2RS	20	47	18	16400	4100	0.138
2205	25	52	18	15200	3900	0.160
2205-2RS	25	52	18	15200	3900	0.160
2205K	25	52	18	15200	3900	0.160
2206	30	62	20	15200	4600	0.260
2206-2RS	30	62	20	15200	4600	0.260
2206K	30	62	20	15200	4600	0.260
2206K-2RS	30	62	20	15200	4600	0.260
2207	35	72	23	21800	6650	0.405
2207-2RS	35	72	23	21800	6650	0.405
2207K	35	72	23	21800	6650	0.405
2208	40	80	23	22500	7380	0.505



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

SUFFIX 2RS = 2 RUBBER SEALS

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
2208-2RS	40	80	23	22500	7380	0.505
2208K	40	80	23	22500	7380	0.505
2209	45	85	23	23200	8000	0.540
2209-2RS	45	85	23	23200	8000	0.540
2209K	45	85	23	23200	8000	0.540
2210	50	90	23	23200	8450	0.580
2210-2RS	50	90	23	23200	8450	0.580
2210K	50	90	23	23200	8450	0.580
2211	55	100	25	26800	9950	0.800
2211-2RS	55	100	25	26800	9950	0.810
2211K	55	100	25	26800	9950	0.810
2221	60	110	28	34000	12500	1.090
2212-2RS	60	110	28	34000	12500	1.090
2212K	60	110	28	34000	12500	1.090
2213	65	120	31	43500	16200	1.450
2213-2RS	65	120	31	43500	16200	1.500
2213K	65	120	31	43500	16200	1.500
2214	70	125	31	44000	17000	1.500
2214-2RS	70	125	31	44000	17000	1.580
2214K	70	125	31	44000	17000	1.500
2215	75	130	31	44200	18000	1.600



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

SUFFIX 2RS = 2 RUBBER SEALS

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
2215-2RS	75	130	31	44200	18000	1.670
2215K	75	130	31	44200	18000	1.600
2216	80	140	33	48800	20200	2.150
2216K	80	140	33	48800	20200	2.150
2217	85	150	36	58200	23500	2.670
2217K	85	150	36	58200	23500	2.670
2302	15	42	17	11800	2800	0.108
2302-2RS	15	42	17	11800	2800	0.108
2303	17	47	19	14300	3500	0.171
2303-2RS	17	47	19	14300	3500	0.171
2304	20	52	21	17800	4750	0.210
2304-2RS	20	52	21	17800	4750	0.220
2305	25	62	24	24500	6480	0.335
2305-2RS	25	62	24	24500	6480	0.354
2306	30	72	27	31500	8680	0.500
2306-2RS	30	72	27	31500	8680	0.500
2306K	30	72	27	31500	8680	0.500
2307	35	80	31	39200	11000	0.675
2307-2RS	35	80	31	39200	11000	0.675
2307K	35	80	31	39200	11000	0.675
2308	40	90	33	44800	13200	0.925



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

SUFFIX 2RS = 2 RUBBER SEALS

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
2308-2RS	40	90	33	44800	13200	0.925
2308K	40	90	33	44800	13200	0.925
2309	45	100	36	55000	16200	1.230
2309-2RS	45	100	36	55000	16200	1.230
2309K	45	100	36	55000	16200	1.230
2310	50	110	40	64500	19800	1.630
2310-2RS	50	110	40	64500	19800	1.630
2310K	50	110	40	64500	19800	1.630
2311	55	120	43	75200	23500	2.090
2311-2RS	55	120	43	75200	23500	2.120
2311K	55	120	43	75200	23500	2.090
2312	60	130	46	86800	27500	2.600
2312-2RS	60	130	46	86800	27500	2.620
2312K	60	130	46	86800	27500	2.600
2313	65	140	48	96000	32500	3.200
2313K	65	140	48	96000	32500	3.200
2314	70	150	51	110000	37500	3.920
2314K	70	150	51	110000	37500	3.920
2315	75	160	55	122000	42800	4.780
2315K	75	160	55	122000	42800	4.780