

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6000	100	10	26	8	4620	1960	29000	34000	0.0200
6000-ZZ	80100	10	26	8	4620	1960	29000	34000	0.0200
6000-2RS	180100	10	26	8	4620	1960	19000	-	0.0200
6001	101	12	28	8	5070	2360	26000	30000	0.0210
6001-ZZ	80101	12	28	8	5070	2360	26000	30000	0.0210
6001-2RS	180101	12	28	8	5070	2360	17000	-	0.0210
6002	102	15	32	9	5590	2850	22000	26000	0.0320
6002-ZZ	80102	15	32	9	5590	2850	22000	26000	0.0320
6002-2RS	180102	15	32	9	5590	2850	16000	-	0.0320
6003	103	17	35	10	6050	3250	20000	24000	0.0390
6003-ZZ	80103	17	35	10	6050	3250	20000	24000	0.0390
6003-2RS	180103	17	35	10	6050	3250	12000	-	0.0390
6004	104	20	42	12	9360	5000	18000	21000	0.0700
6004-ZZ	80104	20	42	12	9360	5000	18000	21000	0.0700
6004-2RS	180104	20	42	12	9360	5000	10000	-	0.0700
6005	105	25	47	12	11200	6550	15000	18000	0.0820
6005-ZZ	80105	25	47	12	11200	6550	15000	18000	0.0820
6005-2RS	180105	25	47	12	11200	6550	9000	-	0.0820
6006	106	30	55	13	13300	8300	13000	15000	0.1240
6006-ZZ	80106	30	55	13	13300	8300	13000	15000	0.1240
6006-2RS	180106	30	55	13	13300	8300	7500	-	0.1240
6007	107	35	62	14	15900	10200	12000	14000	0.1610
6007 -ZZ	80107	35	62	14	15900	10200	12000	14000	0.1610
6007-2RS	180107	35	62	14	15900	10200	6500	-	0.1610
6008	108	40	68	15	16800	11600	10000	12000	0.1970
6008-ZZ	80108	40	68	15	16800	11600	10000	12000	0.1970
6008-2RS	180108	40	68	15	16800	11600	5800	-	0.1970
6009	109	45	75	16	20800	14600	9200	11000	0.2540
6009-ZZ	80109	45	75	16	20800	14600	9200	11000	0.2540
6009-2RS	180109	45	75	16	20800	14600	5300	-	0.2540
6010	110	50	80	16	21600	16000	8400	9800	0.2790
6010-ZZ	80110	50	80	16	21600	16000	8400	9800	0.2790
6010-2RS	180110	50	80	16	21600	16000	4800	-	0.2790
6011	111	55	90	18	28100	21200	7700	9000	0.4050
6011-ZZ	80111	55	90	18	28100	21200	7700	9000	0.4050
6011-2RS	180111	55	90	18	28100	21200	4300	-	0.4050
6012	112	60	95	18	29600	23200	7000	8300	0.4280
6012-ZZ	80112	60	95	18	29600	23200	7000	8300	0.4280
6012-2RS	180112	60	95	18	29600	23200	4000	-	0.4280
6013	113	65	100	18	30700	25000	6500	7700	0.4580
6013-ZZ	80113	65	100	18	30700	25000	6500	7700	0.4580
6013-2RS	180113	65	100	18	30700	25000	3700	-	0.4580
6014	114	70	110	20	37700	31000	6100	7100	0.6350
6014-ZZ	80114	70	110	20	37700	31000	3500	-	0.6350
6014-2RS	180114	70	110	20	37700	31000	3500	-	0.6350
6015	115	75	115	20	39700	33500	5700	6700	0.6730
6015-ZZ	80115	75	115	20	39700	33500	5700	6700	0.6730
6015-2RS	180115	75	115	20	39700	33500	3300	-	0.6730
6016	116	80	125	22	47500	40000	5300	6200	0.8770
6016-ZZ	80116	80	125	22	47500	40000	5300	6200	0.8770
6016-2RS	180116	80	125	22	47500	40000	3100	-	0.8770
6017	117	85	130	22	49400	43000	5000	5900	0.9320
6017-ZZ	80117	85	130	22	49400	43000	5000	5900	0.9320
6017-2RS	180117	85	130	22	49400	43000	2900	-	0.9320
6018	118	90	140	24	58500	50000	4700	5600	1.1900

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6018-ZZ	80118	90	140	24	58500	50000	4700	5600	1.1900
6018-2RS	180118	90	140	24	58500	50000	2700	-	1.1900
6019	119	95	145	24	60500	54000	4500	5300	1.2470
6019-ZZ	80119	95	145	24	60500	54000	4500	5300	1.2470
6019-2RS	180119	95	145	24	60500	54000	2500	-	1.2470
6020	120	100	150	24	60500	54000	4200	5000	1.3400
6020-ZZ	80120	100	150	24	60500	54000	4200	5000	1.3400
6020-2RS	180120	100	150	24	60500	54000	2400	-	1.3400
6021	121	105	160	26	72800	65500	4000	4700	1.6900
6021-ZZ	80121	105	160	26	72800	65500	4000	4700	1.6900
6021-2RS	180121	105	160	26	72800	65500	2300	-	1.6900
6022	122	110	170	28	81900	73500	3800	4500	2.0230
6022-ZZ	80122	110	170	28	81900	73500	3800	4500	2.0230
6022-2RS	180122	110	170	28	81900	73500	2200	-	2.0230
6024	124	120	180	28	85200	80000	3200	3800	2.2130
6024 -ZZ	80124	120	180	28	85200	80000	3200	3800	2.2130
6024-2RS	180124	120	180	28	85200	80000	2100	-	2.2130
6026	126	130	200	33	104000	100000	3200	3800	3.2700
6026-ZZ	80126	130	200	33	104000	100000	3200	3800	3.2700
6026-2RS	180126	130	200	33	104000	100000	1900	-	3.2700
6028	128	140	210	33	110000	109000	3000	3500	3.5470
6028-ZZ	80128	140	210	33	110000	109000	3000	3500	3.5470
6028-2RS	180128	140	210	33	110000	109000	1800	-	3.5470
6030	130	150	225	35	131000	124000	2800	3200	4.8800
6030-ZZ	80130	150	225	35	131000	124000	2800	3200	4.8800
6030-2RS	180130	150	225	35	131000	124000	1600	-	4.8800
6032	132	160	240	38	136000	135000	2600	3000	6.0730
6032 -ZZ	80132	160	240	38	136000	135000	2600	3000	6.0730
6032-2RS	180132	160	240	38	136000	135000	1500	-	6.0730
6034	134	170	260	42	168000	173000	2400	2800	7.1750
6034 -ZZ	80134	170	260	42	168000	173000	2400	2800	7.1750
6036	136	180	280	46	180000	184000	2300	2700	10.5600
6036 -ZZ	80136	180	280	46	180000	184000	2300	2700	10.5600
6038	138	190	290	46	188000	200000	2100	2500	11.0700
6038 -ZZ	80138	190	290	46	188000	200000	2100	2500	11.0700
6040	140	200	310	51	201000	222000	2000	2400	14.1000
6044	144	220	340	56	247000	290000	1800	2200	18.5000
6048	148	240	360	56	255000	315000	1700	2000	20.0000

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6200	200	10	30	9	5070	2360	25000	30000	0.0310
6200-ZZ	80200	10	30	9	5070	2360	25000	30000	0.0310
6200-2RS	180200	10	30	9	5070	2360	17000	-	0.0310
6201	201	12	32	10	6890	3100	22000	26000	0.0380
6201-ZZ	80201	12	32	10	6890	3100	22000	26000	0.0380
6201-2RS	180201	12	32	10	6890	3100	15000	-	0.0380
6202	202	15	35	11	7800	3750	19000	23000	0.0440
6202-ZZ	80202	15	35	11	7800	3750	19000	23000	0.0440
6202-2RS	180202	15	35	11	7800	3750	13000	-	0.0440
6203	203	17	40	12	9560	4750	18000	21000	0.0660
6203 -ZZ	80203	17	40	12	9560	4750	18000	21000	0.0660
6203-2RS	180203	17	40	12	9560	4750	12000	-	0.0660
6204	204	20	47	14	12700	6550	16000	18000	0.1090
6204 -ZZ	80204	20	47	14	12700	6550	16000	18000	0.1090
6204-2RS	180204	20	47	14	12700	6550	10000	-	0.1090
6205	205	25	52	15	14000	7800	13000	15000	0.1330
6205-ZZ	80205	25	52	15	14000	7800	13000	15000	0.1330
6205-2RS	180205	25	52	15	14000	7800	8500	-	0.1330
6206	206	30	62	16	19500	11200	11000	13000	0.2000
6206-ZZ	80206	30	62	16	19500	11200	11000	13000	0.2000
6206-2RS	180206	30	62	16	19500	11200	7500	-	0.2000
6207	207	35	72	17	25500	15300	9800	11000	0.2990
6207 -ZZ	80207	35	72	17	25500	15300	9800	11000	0.2990
6207-2RS	180207	35	72	17	25500	15300	6300	-	0.2990
6208	208	40	80	18	30700	19000	8700	10000	0.3790
6208-ZZ	80208	40	80	18	30700	19000	8700	10000	0.3790
6208-2RS	180208	40	80	18	30700	19000	5600	-	0.3790
6209	209	45	85	19	33200	21600	7800	9200	0.4300
6209-ZZ	80209	45	85	19	33200	21600	7800	9200	0.4300
6209-2RS	180209	45	85	19	33200	21600	5000	-	0.4300
6210	210	50	90	20	35100	23200	7100	8300	0.4750
6210-ZZ	80210	50	90	20	35100	23200	7100	8300	0.4750
6210-2RS	180210	50	90	20	35100	23200	4800	-	0.4750
6211	211	55	100	21	43600	29000	6400	7600	0.6250
6211-ZZ	80211	55	100	21	43600	29000	6400	7600	0.6250
6211-2RS	180211	55	100	21	43600	29000	4300	-	0.6250
6212	212	60	110	22	47500	32500	6000	7000	0.7970
6212-ZZ	80212	60	110	22	47500	32500	6000	7000	0.7970
6212-2RS	180212	60	110	22	47500	32500	3700	-	0.7970
6213	213	65	120	23	55900	40500	5500	6500	1.0170
6213-ZZ	80213	65	120	23	55900	40500	5500	6500	1.0170
6213-2RS	180213	65	120	23	55900	40500	3500	-	1.0170
6214	214	70	125	24	60500	45000	5100	6000	1.1100
6214-ZZ	80214	70	125	24	60500	45000	5100	6000	1.1100
6214-2RS	180214	70	125	24	60500	45000	3300	-	1.1100
6215	215	75	130	25	66300	49000	4800	5600	1.2100
6215-ZZ	80215	75	130	25	66300	49000	4800	5600	1.2100
6215-2RS	180215	75	130	25	66300	49000	3100	-	1.2100
6216	216	80	140	26	70200	55000	4500	5300	1.4600
6216-ZZ	80216	80	140	26	70200	55000	4500	5300	1.4600
6216-2RS	180216	80	140	26	70200	55000	2900	-	1.4600
6217	217	85	150	28	83200	64000	4200	5000	1.8470
6217-ZZ	80217	85	150	28	83200	64000	4200	5000	1.8470
6217-2RS	180217	85	150	28	83200	64000	2700	-	1.8470
6218	218	90	160	30	95600	73500	4000	4700	2.2230

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. CO	Grease	Oil	
6218-ZZ	80218	90	160	30	95600	73500	2600	-	2.2230
6218-2RS	180218	90	160	30	95600	73500	2600	-	2.2230
6219	219	95	170	32	108000	81500	3700	4400	2.7130
6219-ZZ	80219	95	170	32	108000	81500	3700	4400	2.7130
6219-2RS	180219	95	170	32	108000	81500	2400	-	2.7130
6220	220	100	180	34	124000	93000	3500	4200	3.3210
6220-ZZ	80220	100	180	34	124000	93000	3500	4200	3.3210
6220-2RS	180220	100	180	34	124000	93000	2300	-	3.3210
6221	221	105	190	36	133000	104000	3400	4000	3.7170
6221-ZZ	80221	105	190	36	133000	104000	3400	4000	3.7170
6221-2RS	180221	105	190	36	133000	105000	2200	-	3.7170
6222	222	110	200	38	143000	118000	3200	3800	4.3400
6222 -ZZ	80222	110	200	38	143000	118000	3200	3800	4.3400
6222-2RS	180222	110	200	38	143000	118000	2000	-	4.3400
6224	224	120	215	40	148000	131000	2900	3400	5.1000
6224 -ZZ	80224	120	215	40	148000	131000	2900	3400	5.1000
6224-2RS	180224	120	215	40	148000	131000	1900	-	5.1000
6226	226	130	230	40	156000	146000	2700	3100	5.6150
6226-ZZ	80226	130	230	40	156000	146000	2700	3100	5.6150
6228	228	140	250	42	165000	150000	2500	2900	7.4850
6228 -ZZ	80228	140	250	42	165000	150000	2500	2900	7.4850
6230	230	150	270	45	174000	166000	2300	2700	9.4750
6230 -ZZ	80230	150	270	45	174000	166000	2300	2700	9.4750
6232	232	160	290	48	186000	186000	2100	2500	14.5900
6232 -ZZ	80232	160	290	48	186000	186000	2100	2500	14.5900
6234	234	170	310	52	212000	224000	2000	2400	17.5700
6234-ZZ	80234	170	310	52	212000	224000	2000	2400	17.5700
6236	236	180	320	52	229000	240000	1900	2200	18.6000
6236 -ZZ	80236	180	320	52	229000	240000	1900	2200	18.6000
6238	238	190	340	55	255000	280000	1800	2100	22.8000
6240	240	200	360	58	270000	310000	1700	2000	28.0000

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6300-ZZ	80300	10	35	11	8060	3400	23000	27000	0.0540
6300-2RS	180300	10	35	11	8060	3400	15000	-	0.0540
6301	301	12	37	12	9750	4150	20000	24000	0.0630
6301-ZZ	80301	12	37	12	9750	4150	20000	24000	0.0630
6301-2RS	180301	12	37	12	9750	4150	14000	-	0.0630
6302	302	15	42	13	11400	5400	17000	21000	0.0870
6302 -ZZ	80302	15	42	13	11400	5400	17000	21000	0.0870
6302-2RS	180302	15	42	13	11400	5400	12000	-	0.0870
6303	303	17	47	14	13500	6550	16000	19000	0.1170
6303 -ZZ	80303	17	47	14	13500	6550	16000	19000	0.1170
6303-2RS	180303	17	47	14	13500	6550	11000	-	0.1170
6304	304	20	52	15	15900	7800	14000	17000	0.1530
6304 -ZZ	80304	20	52	15	15900	7800	14000	17000	0.1530
6304-2RS	180304	20	52	15	15900	7800	9500	-	0.1530
6305	305	25	62	17	22500	11600	12000	14000	0.2380
6305 -ZZ	80305	25	62	17	22500	11600	12000	14000	0.2380
6305-2RS	180305	25	62	17	22500	11600	7500	-	0.2380
6306	80306	30	72	19	28100	16000	10000	12000	0.3600
6306 -ZZ	80306	30	72	19	28100	16000	10000	12000	0.3600
6306-2RS	180306	30	72	19	28100	16000	6300	-	0.3600
6307	307	35	80	21	33200	19000	8800	10000	0.4670
6307-ZZ	80307	35	80	21	33200	19000	8800	10000	0.4670
6307-2RS	180307	35	80	21	33200	19000	6000	-	0.4670
6308	308	40	90	23	41000	24000	7800	9200	0.6400
6308 -ZZ	80308	40	90	23	41000	24000	7800	9200	0.6400
6308-2RS	180308	40	90	23	41000	24000	5000	-	0.6400
6309	309	45	100	25	52700	31500	7000	8200	0.8430
6309 -ZZ	80309	45	100	25	52700	31500	7000	8200	0.8430
6309-2RS	180309	45	100	25	52700	31500	4500	-	0.8430
6310	310	50	110	27	61800	38000	6400	7500	1.0970
6310-ZZ	80310	50	110	27	61800	38000	6400	7500	1.0970
6310-2RS	180310	50	110	27	61800	38000	4300	-	1.0970
6311	311	55	120	29	71500	45000	5800	6800	1.3770
6311-ZZ	80311	55	120	29	71500	45000	5800	6800	1.3770
6311-2RS	180311	55	120	29	71500	45000	3800	-	1.3770
6312	312	60	130	31	81900	52000	5400	6300	1.7330
6312-ZZ	80312	60	130	31	81900	52000	5400	6300	1.7330
6312-2RS	180312	60	130	31	81900	52000	3400	-	1.7330
6313	313	65	140	33	92300	60000	4900	5800	2.1530
6313-ZZ	80313	65	140	33	92300	60000	4900	5800	2.1530
6313-2RS	180313	65	140	33	92300	60000	3200	-	2.1530
6314	314	70	150	35	104000	68000	4600	5400	2.5600
6314-ZZ	80314	70	150	35	104000	68000	4600	5400	2.5600
6314-2RS	180314	70	150	35	104000	68000	3000	-	2.5600
6315	315	75	160	37	111400	76500	4300	5000	3.1200
6315-ZZ	80315	75	160	37	111400	76500	4300	5000	3.1200
6315-2RS	180315	75	160	37	111400	76500	2800	-	3.1200
6316	316	80	170	39	124000	86500	4000	4700	3.6800
6316-ZZ	80316	80	170	39	124000	86500	4000	4700	3.6800
6316-2RS	180316	80	170	39	124000	86500	2700	-	3.6800
6317	317	85	180	41	133000	96500	3800	4500	4.3030
6317-ZZ	80317	85	180	41	133000	96500	3800	4500	4.3030
6317-2RS	180317	85	180	41	133000	96500	2500	-	4.3030
6318	318	90	190	43	143000	108000	3600	4200	4.9670
6318-ZZ	80318	90	190	43	143000	108000	3600	4200	4.9670

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6318-2RS	180318	90	190	43	143000	108000	2400	-	4.9670
6319	319	95	200	45	153000	118000	3300	3900	5.7100
6319-ZZ	80319	95	200	45	153000	118000	3300	3900	5.7100
6319-2RS	180319	95	200	45	153000	118000	2200	-	5.7100
6320	320	100	215	47	174000	140000	3200	3700	7.6330
6320 -ZZ	80320	100	215	47	174000	140000	3200	3700	7.6330
6320-2RS	180320	100	215	47	174000	140000	2100	-	7.6330
6321	321	105	225	49	182000	153000	3000	3600	8.6770
6321-ZZ	80321	105	225	49	182000	153000	3000	3600	8.6770
6321-2RS	180321	105	225	49	182000	153000	1900	-	8.6770
6322	322	110	240	50	203000	180000	2900	3400	9.6030
6322 -ZZ	80322	110	240	50	203000	180000	2900	3400	9.6030
6322-2RS	180322	110	240	50	203000	180000	1600	-	9.6030
6324	324	120	260	55	208000	186000	2600	3100	12.7500
6324-ZZ	80324	120	260	55	208000	186000	2600	3100	12.7500
6326	326	130	280	58	230000	216000	2400	2800	18.4000
6326 -ZZ	80326	130	280	58	230000	216000	2400	2800	18.4000
6328	328	140	300	62	251000	245000	2200	2600	22.0000
6328 -ZZ	80328	140	300	62	251000	245000	2200	2600	22.0000
6330	330	150	320	65	276000	285000	2000	2400	23.0000
6332	332	160	340	68	285000	300000	1900	2300	29.0000

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6403	403	17	62	17.000	22900	10800	13000	15000	0.2700
6403-ZZ	80403	17	62	17.000	22900	10800	13000	15000	0.2700
6403 -2RS	180403	17	62	17.000	22900	10800	8000	-	0.2700
6404	404	20	72	19.000	31000	15200	9500	12000	0.4000
6404-ZZ	80404	20	72	19.000	31000	15200	9500	12000	0.4000
6404 -2RS	180404	20	72	19.000	31000	15200	6300	-	0.4000
6405	405	25	80	21.000	35800	19300	8500	10000	0.5300
6405-ZZ	80405	25	80	21.000	35800	19300	8500	10000	0.5300
6405 -2RS	180405	25	80	21.000	35800	19300	5600	-	0.5300
6406	406	30	90	23.000	43600	23600	7500	9000	0.7400
6406-ZZ	80406	30	90	23.000	43600	23600	7500	9000	0.7400
6406 -2RS	180406	30	90	23.000	43600	23600	5000	-	0.7400
6407	407	35	100	25.000	55300	31000	6700	8000	0.9500
6407-ZZ	80407	35	100	25.000	55300	31000	6700	8000	0.9500
6407-2RS	180407	35	100	25.000	55300	31000	4500	-	0.9500
6408	408	40	110	27.000	63700	36500	6000	7000	1.2500
6408-ZZ	80408	40	110	27.000	63700	36500	6000	7000	1.2500
6408 -2RS	180408	40	110	27.000	63700	36500	4000	-	1.2500
6409	409	45	120	29.000	76100	45000	5300	6300	1.5500
6409-ZZ	80409	45	120	29.000	76100	45000	5300	6300	1.5500
6409 -2RS	180409	45	120	29.000	76100	45000	3600	-	1.5500
6410	410	50	130	31.000	87100	52000	5000	6000	1.9000
6410-ZZ	80410	50	130	31.000	87100	52000	5000	6000	1.9000
6410-2RS	180410	50	130	31.000	87100	52000	3400	-	1.9000
6411	411	55	140	33.000	99500	62000	4500	5300	2.3000
6411-ZZ	80411	55	140	33.000	99500	62000	4500	5300	2.3000
6411-2RS	180411	55	140	33.000	99500	62000	3000	-	2.3000
6412	412	60	150	35.000	108000	69500	4300	5000	2.7500
6412-ZZ	80412	60	60	150	108000	69500	4300	5000	2.7500
6412-2RS	180412	60	60	150	108000	69500	2800	-	2.7500
6413	413	65	65	160	119000	78000	4000	4800	3.3000
6413-ZZ	80413	65	65	160	119000	78000	4000	4800	3.3000
6413-2RS	180413	65	65	160	119000	78000	2600	-	3.3000
6414	414	70	70	180	143000	10400	3800	4500	4.8500
6414-ZZ	80414	70	70	180	143000	10400	3800	4500	4.8500
6414-2RS	180414	70	70	180	143000	10400	2500	-	4.8500
6415	415	75	75	190	153000	114000	3700	4400	6.8000
6415-ZZ	80415	75	75	190	153000	114000	3700	4400	6.8000
6415-2RS	180415	75	75	190	153000	114000	2300	-	6.8000
6416	416	80	80	200	162000	125000	3600	4200	6.4220
6416-ZZ	80416	80	80	200	162000	125000	3600	4200	6.4220
6416-2RS	180416	80	80	200	162000	125000	2100	-	6.4220
6417	417	85	85	210	174000	137000	3400	4000	9.5000
6417-ZZ	80417	85	85	210	174000	137000	3400	4000	9.5000
6417-2RS	180417	85	85	210	174000	137000	1800	-	9.5000
6418	418	90	90	225	186000	150000	3200	3800	9.5600

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
62200-2RS	180500	10	30	14	5100	2400	17000	-	0.0450
62201-2RS	180501	12	32	14	6900	3100	15000	-	0.0480
62202-2RS	180502	15	35	14	7800	3750	13000	-	0.0540
62203-2RS	180503	17	40	16	9500	4750	12000	-	0.0830
62204-2RS	180504	20	47	18	12700	6550	10000	-	0.1300
62205-2RS	180505	25	52	18	14000	7800	8500	-	0.1500
62206-2RS	180506	30	62	20	16500	11200	7500	-	0.2430
62207-2RS	180507	35	72	23	25500	15300	6300	-	0.3880
62208-2RS	180508	40	80	23	30700	19000	5600	-	0.4710
62209-2RS	180509	45	85	23	33200	21600	5000	-	0.5230
62210-2RS	180510	50	90	23	35100	23200	4800	-	0.5500
62211-2RS	180511	55	100	25	43600	29000	4300	-	0.7000
62212-2RS	180512	60	110	28	47500	32500	4000	-	0.9700
62213-2RS	180513	65	120	31	55900	40500	3600	-	1.2500
62214-2RS	180514	70	125	31	60500	45000	3400	-	1.3000
62300-2RS	180600	10	35	17	8000	3400	15000	-	0.0600
62301-2RS	180601	12	37	17	9750	4150	14000	-	0.0700
62302-2RS	180602	15	42	17	11400	5400	12000	-	0.1100
62303-2RS	180603	17	47	19	13500	6550	11000	-	0.1500
62304-2RS	180604	20	52	21	15900	7800	9500	-	0.2070
62305-2RS	180605	25	62	24	22500	11600	7500	-	0.3260
62306-2RS	180606	30	72	27	28100	16000	6300	-	0.4930
62307 -2RS	180607	35	80	31	33200	19000	6000	-	0.6800
62308-2RS	180608	40	90	33	41000	24000	5000	-	0.8900
62309-2RS	180609	45	100	36	52700	31500	4500	-	1.1900
62310-2RS	180610	50	110	40	61800	38000	4300	-	1.5000
62311-2RS	180611	55	120	43	71500	45000	3800	-	1.9500
62312-2RS	180612	60	130	46	81900	52000	3400	-	2.5000
62313-2RS	180613	65	140	48	92300	60000	3200	-	3.0000
62314-2RS	180614	70	150	51	104000	68000	3000	-	3.5500

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
16001	7000101	12	28	7	5100	2390	26000	30000	0.0220
16001-ZZ	7000101-ZZ	12	28	7	5100	2390	26000	30000	0.0220
16001-2RS	7000101-2RS	12	28	7	5100	2390	26000	-	0.0220
16002	7000102	15	32	8	5590	2850	22000	26000	0.0250
16002-ZZ	7000102-ZZ	15	32	8	5590	2850	22000	26000	0.0250
16002-2RS	7000102-2RS	15	32	8	5590	2850	22000	-	0.0250
16003	7000103	17	35	8	6050	3250	20000	24000	0.0320
16003-ZZ	7000103-ZZ	17	35	8	6050	3250	20000	24000	0.0320
16003-2RS	7000103-2RS	17	35	8	6050	3250	20000	-	0.0320
16004	7000104	20	42	8	6890	4500	18000	21000	0.0500
16004-ZZ	7000104-ZZ	20	42	8	6890	4500	18000	21000	0.0500
16004-2RS	7000104-2RS	20	42	8	6890	4500	18000	-	0.0500
16005	7000105	25	47	8	7610	4750	15000	18000	0.0600
16005-ZZ	7000105-ZZ	25	47	8	7610	4750	15000	18000	0.0600
16005-2RS	7000105-2RS	25	47	8	7610	4750	15000	-	0.0600
16006	7000106	30	55	9	11200	7350	13000	15000	0.0850
16006-ZZ	7000106-ZZ	30	55	9	11200	7350	13000	15000	0.0850
16006-2RS	7000106-2RS	30	55	9	11200	7350	13000	-	0.0850
16007	7000107	35	62	9	12400	8150	12000	14000	0.1100
16007-ZZ	7000107-ZZ	35	62	9	12400	8150	12000	14000	0.1100
16007-2RS	7000107-2RS	35	62	9	12400	8150	12000	-	0.1100
16008	7000108	40	68	9	13300	9150	10000	12000	0.1300
16008-ZZ	7000108-ZZ	40	68	9	13300	9150	10000	12000	0.1300
16008-2RS	7000108-2RS	40	68	9	13300	9150	10000	-	0.1300
16009	7000109	45	75	10	15600	10800	9200	11000	0.1700
16009-ZZ	7000109-ZZ	45	75	10	15600	10800	9200	11000	0.1700
16009-2RS	7000109-2RS	45	75	10	15600	10800	9200	-	0.1700
16010	7000110	50	80	10	16300	11400	8400	9800	0.1800
16010-ZZ	7000110-ZZ	50	80	10	16300	11400	8400	9800	0.1800
16010-2RS	7000110-2RS	50	80	10	16300	11400	8400	-	0.1800
16011	7000111	55	90	11	19500	14000	7700	9000	0.2600
16012	7000112	60	95	11	19900	15000	7000	8300	0.2800
16013	7000113	65	100	11	21200	16600	6500	7700	0.3000
16014	7000114	70	110	13	27800	25000	6000	7100	0.4300
16015	7000115	75	115	13	28600	27000	5600	6600	0.4600
16016	7000116	80	125	14	33200	31500	5300	6200	0.6000
16017	7000117	85	130	14	33800	33500	5000	5900	0.6300
16018	7000118	90	140	16	33500	33500	4700	5600	0.8500
16019	7000119	95	145	16	34500	35000	4500	5300	0.8900
16020	7000120	100	150	16	44200	44000	4200	5000	0.9100
16021	7000121	105	160	18	52000	51000	4000	4700	1.2000
16022	7000122	110	170	19	57200	57000	3800	4500	1.4500
16024	7000124	120	180	19	60500	64000	3500	4100	1.6000
16026	7000126	130	200	22	79300	81500	3200	3800	2.3500
16028	7000128	140	210	22	80600	86500	3000	3500	2.5000
16030	7000130	150	225	24	92300	98000	2800	3200	3.1500
16032	7000132	160	240	25	99500	108000	2600	3000	3.7000
16034	7000134	170	260	28	119000	129000	2400	2800	5.0000
16036	7000136	180	280	31	138000	146000	2300	2700	6.6000
16038	7000138	190	290	31	148000	166000	2100	2500	7.9000
16040	7000140	200	310	34	168000	190000	2000	2400	8.8500
16044	7000144	220	340	37	174000	204000	1800	2200	11.5000
16048	7000148	240	360	37	178000	217000	1700	2000	12.1000
16052	7000152	260	400	44	227000	299000	1500	1800	18.5000
16056	7000156	280	420	44	232000	315000	1400	1600	23.0000

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
16100		10	28	8	4800	2100	29000	35000	0.0230
16100-2RS	16100DDU	10	28	8	4800	2100	29000	-	0.0240
16100-ZZ	16100-2Z	10	28	8	4800	2100	29000	-	0.0240
16101		12	30	8	4950	2180	28000	33000	0.0250
16101-2RS	16101DDU	12	30	8	4950	2180	17000	-	0.0260
16101-ZZ	16101-2Z	12	30	8	4950	2180	28000	-	0.0260

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
61700	6700	10	15	3	855	435	15000	17000	0.0014
61700-2RS	6700-2RS	10	15	4	855	435	10000	-	0.0015
61700-ZZ	6700-ZZ	10	15	4	855	435	15000	17000	0.0015
61701	6701	12	18	4	930	530	13000	15000	0.0030
61701-2RS	6701-2RS	12	18	4	930	530	9000	-	0.0030
61701-ZZ	6701-ZZ	12	18	4	930	530	13000	15000	0.0030
61702	6702	15	21	4	940	585	11000	13000	0.0035
61702-2RS	6702-2RS	15	21	4	940	585	8000	-	0.0035
61702-ZZ	6702-ZZ	15	21	4	940	585	11000	13000	0.0035
61703	6703	17	23	4	1000	658	9500	11000	0.0040
61703-2RS	6703-2RS	17	23	4	1000	658	6600	-	0.0040
61703-ZZ	6703-ZZ	17	23	4	1000	658	9500	11000	0.0040
61704	6704	20	27	4	1400	730	8500	10000	0.0060
61704-2RS	6704-2RS	20	27	4	1400	730	6000	-	0.0060
61704-ZZ	6704-ZZ	20	27	4	1400	730	8500	10000	0.0060
61705	6705	25	32	4	1100	840	7000	8000	0.0071
61705-2RS	6705-2RS	25	32	4	1100	840	4800	-	0.0071
61705-ZZ	6705-ZZ	25	32	4	1100	840	7000	8000	0.0071
61706	6706	30	37	4	1140	950	5500	7000	0.0085
61706-2RS	6706-2RS	30	37	4	1140	950	4200	-	0.0085
61706-ZZ	6706-ZZ	30	37	4	1140	950	5500	7000	0.0085
61707	6707	35	44	5	1866	1635	4900	6000	0.0150
61707-2RS	6707-2RS	35	44	5	1866	1635	3600	-	0.0150
61707-ZZ	6707-ZZ	35	44	5	1866	1635	4900	6000	0.0150
61708	6708	40	50	6	2516	2233	4300	5000	0.0230
61708-2RS	6708-2RS	40	50	6	2516	2233	3200	-	0.0230
61708-ZZ	6708-ZZ	40	50	6	2516	2233	4300	5000	0.0230
61709	6709	45	55	6	2580	2397	3900	4600	0.0270
61709-2RS	6709-2RS	45	55	6	2580	2397	3000	-	0.0270
61709-ZZ	6709-ZZ	45	55	6	2580	2397	3900	4600	0.0270
61710-2RS	6710-2RS	50	62	6	2670	2640	2500	-	0.0520

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6800	61800	10	19	5	1380	585	32000	38000	0.0050
6800-ZZ	61800-ZZ	10	19	5	1380	585	32000	38000	0.0050
6800-2RS	61800-2RS	10	19	5	1380	585	20000	-	0.0050
6801	61801	12	21	5	1430	670	29000	35000	0.0060
6801-ZZ	61801-ZZ	12	21	5	1430	670	29000	35000	0.0060
6801-2RS	61801-2RS	12	21	5	1430	670	19000	-	0.0060
6802	61802	15	24	5	1560	800	26000	31000	0.0070
6802-ZZ	61802-ZZ	15	24	5	1560	800	26000	31000	0.0070
6802-2RS	61802-2RS	15	24	5	1560	800	17000	-	0.0070
6803	61803	17	26	5	1680	930	24000	28000	0.0080
6803-ZZ	61803-ZZ	17	26	5	1680	930	24000	28000	0.0080
6803 -2RS	61803 -2RS	17	26	5	1680	930	16000	-	0.0080
6804	61804	20	32	7	2700	1500	21000	25000	0.0180
6804-ZZ	61804-ZZ	20	32	7	2700	1500	21000	25000	0.0180
6804 -2RS	61804 -2RS	20	32	7	2700	1500	13000	-	0.0180
6805	61805	25	37	7	4360	2600	18000	21000	0.0220
6805-ZZ	61805-ZZ	25	37	7	4360	2600	18000	21000	0.0220
6805-2RS	61805-2RS	25	37	7	4360	2600	11000	-	0.0220
6806	61806	30	42	7	4490	2900	15000	18000	0.0270
6806-ZZ	61806-ZZ	30	42	7	4490	2900	15000	18000	0.0270
6806-2RS	61806-2RS	30	42	7	4490	2900	9500	-	0.0270
6807	61807	35	47	7	4750	3200	13000	16000	0.0300
6807-ZZ	61807-ZZ	35	47	7	4750	3200	13000	16000	0.0300
6807-2RS	61807-2RS	35	47	7	4750	3200	8000	-	0.0300
6808	61808	40	52	7	4940	3450	12000	14000	0.0340
6808-ZZ	61808-ZZ	40	52	7	4940	3450	12000	14000	0.0340
6808-2RS	61808-2RS	40	52	7	4940	3450	7500	-	0.0340
6809	61809	45	58	7	6050	4300	11000	12000	0.0400
6809-ZZ	61809-ZZ	45	58	7	6050	4300	11000	12000	0.0400
6809-2RS	61809-2RS	45	58	7	6050	4300	6700	-	0.0400
6810	61810	50	65	7	6240	4750	9600	11000	0.0520
6810-ZZ	61810-ZZ	50	65	7	6240	4750	9600	11000	0.0520
6810-2RS	61810-2RS	50	65	7	6240	4750	6000	-	0.0520
6811	61811	55	72	9	8320	6200	8700	10000	0.0830
6811-ZZ	61811-ZZ	55	72	9	8320	6200	8700	10000	0.0830
6811-2RS	61811-2RS	55	72	9	8320	6200	5300	-	0.0830
6812	61812	60	78	10	8710	6700	8000	9400	0.1100
6812-ZZ	61812-ZZ	60	78	10	8710	6700	8000	9400	0.1100
6812-2RS	61812-2RS	60	78	10	8710	6700	4800	-	0.1100
6813	61813	65	85	10	12000	11500	7400	8700	0.1300
6813-ZZ	61813-ZZ	65	85	10	12000	11500	7400	8700	0.1300
6813-2RS	61813-2RS	65	85	10	12000	11500	4500	-	0.1300
6814	61814	70	90	10	12100	11900	6900	8100	0.1400
6814-ZZ	61814-ZZ	70	90	10	12100	11900	6900	8100	0.1400
6814-2RS	61814-2RS	70	90	10	12100	11900	4300	-	0.1400
6815	61815	75	95	10	12500	10800	6400	7600	0.1500
6815-ZZ	61815-ZZ	75	95	10	12500	10800	6400	7600	0.1500
6815-2RS	61815-2RS	75	95	10	12500	10800	4000	-	0.1500
6816	61816	80	100	10	13300	12400	6000	7100	0.1550
6816-ZZ	61816-ZZ	80	100	10	13300	12400	6000	7100	0.1550
6816-2RS	61816-2RS	80	100	10	13300	12400	3600	-	0.1550
6817	61817	85	110	13	19500	16600	5700	6700	0.2700
6817-ZZ	61817-ZZ	85	110	13	19500	16600	5700	6700	0.2700
6817-2RS	61817-2RS	85	110	13	19500	16600	3400	-	0.2700
6818	61818	90	115	13	19900	17000	5400	6300	0.2800

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6818-ZZ	61818-ZZ	90	115	13	19900	17000	5400	6300	0.2800
6818-2RS	61818-2RS	90	115	13	19900	17000	3200	-	0.2800
6819	61819	95	120	13	19900	17600	5000	5900	0.3000
6819-ZZ	61819-ZZ	95	120	13	19900	17600	5000	5900	0.3000
6819-2RS	61819-2RS	95	120	13	19900	17600	3000	-	0.3000
6820	61820	100	125	13	19900	18300	4800	5600	0.3100
6820-ZZ	61820-ZZ	100	125	13	19900	18300	4800	5600	0.3100
6820-2RS	61820-2RS	100	125	13	19900	18300	3000	-	0.3100
6821	61821	105	130	13	20800	19600	4600	5400	0.3200
6821-ZZ	61821-ZZ	105	130	13	20800	19600	4600	5400	0.3200
6821-2RS	61821-2RS	105	130	13	20800	19600	2800	-	0.3200
6822	61822	110	140	16	28100	30700	4300	5100	0.6000
6822-ZZ	61822-ZZ	110	140	16	28100	30700	4300	5100	0.6000
6822 -2RS	61822 -2RS	110	140	16	28100	30700	2600	-	0.6000
6824	61824	120	150	16	29000	33000	4000	4700	0.6500
6824-ZZ	61824-ZZ	120	150	16	29000	33000	4000	4700	0.6500
6824 -2RS	61824 -2RS	120	150	16	29000	33000	2400	-	0.6500
6826	61826	130	165	18	39000	43000	3700	4300	0.9300
6826-ZZ	61826-ZZ	130	165	18	39000	43000	3700	4300	0.9300
6826 -2RS	61826 -2RS	130	165	18	39000	43000	2200	-	0.9300
6828	61828	140	175	18	40500	46500	3400	4000	0.9900
6828-ZZ	61828-ZZ	140	175	18	40500	46500	3400	4000	0.9900
6828 -2RS	61828 -2RS	140	175	18	40500	46500	2000	-	0.9900
6830	61830	150	190	20	47500	54500	3100	3700	1.2000
6830-ZZ	61830-ZZ	150	190	20	47500	54500	3100	3700	1.2000
6830-2RS	61830-2RS	150	190	20	47500	54500	3100	-	1.2000
6832	61832	160	200	20	49400	64000	2900	3400	1.3000
6832-ZZ	61832-ZZ	160	200	20	49400	64000	2900	3400	1.3000
6832-2RS	61832-2RS	160	200	20	49400	64000	2900	-	1.3000
6834	61834	170	215	22	61800	78000	2700	3200	1.8500
6834-ZZ	61834-ZZ	170	215	22	61800	78000	2700	3200	1.8500
6834-2RS	61834-2RS	170	215	22	61800	78000	2700	-	1.8500
6836	61836	180	225	22	62400	81500	2600	3000	2.0000
6836-ZZ	61836-ZZ	180	225	22	62400	81500	2600	3000	2.0000
6836-2RS	61836-2RS	180	225	22	62400	81500	2600	-	2.0000
6838	61838	190	240	24	73000	88000	2400	2900	2.6200
6838-ZZ	61838-ZZ	190	240	24	73000	88000	2400	2900	2.6200
6838-2RS	61838-2RS	190	240	24	73000	88000	2400	-	2.6200
6840	61840	200	250	24	76100	102000	2300	2700	2.7000
6840-2RS	61840-2RS	200	250	24	76100	102000	2300	-	2.7000
6844	61844	220	270	24	78000	110000	2100	2400	3.0000
6844-2RS	61844-2RS	220	270	24	78000	110000	2100	-	3.0000
6848	61848	240	300	28	98500	127000	1900	2200	4.6000
6856	61856	280	350	33	138000	200000	1600	1900	7.4000

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6900	61900	10	22	6	1950	750	30000	36000	0.0100
6900-ZZ	61900-ZZ	10	22	6	1950	750	30000	36000	0.0100
6900-2RS	61900-2RS	10	22	6	1950	750	19000	-	0.0100
6901	61901	12	24	6	2250	980	27000	32000	0.0110
6901-ZZ	61901-ZZ	12	24	6	2250	980	27000	32000	0.0110
6901-2RS	61901-2RS	12	24	6	2250	980	18000	-	0.0110
6902	61902	15	28	7	4030	2040	24000	28000	0.0160
6902-ZZ	61902-ZZ	15	28	7	4030	2040	24000	28000	0.0160
6902-2RS	61902-2RS	15	28	7	4030	2040	16000	-	0.0160
6903	61903	17	30	7	4360	2320	22000	26000	0.0180
6903-ZZ	61903-ZZ	17	30	7	4360	2320	22000	26000	0.0180
6903 -2RS	61903 -2RS	17	30	7	4360	2320	14000	-	0.0180
6904	61904	20	37	9	6370	3650	19000	23000	0.0380
6904-ZZ	61904-ZZ	20	37	9	6370	3650	19000	23000	0.0380
6904 -2RS	61904 -2RS	20	37	9	6370	3650	12000	-	0.0380
6905	61905	25	42	9	6630	4000	16000	19000	0.0450
6905-ZZ	61905-ZZ	25	42	9	6630	4000	16000	19000	0.0450
6905-2RS	61905-2RS	25	42	9	6630	4000	10000	-	0.0450
6906	61906	30	47	9	7280	4550	14000	17000	0.0510
6906-ZZ	61906-ZZ	30	47	9	7280	4550	14000	17000	0.0510
6906-2RS	61906-2RS	30	47	9	7280	4550	8500	-	0.0510
6907	61907	35	55	10	9560	6200	12000	15000	0.0800
6907-ZZ	61907-ZZ	35	55	10	9560	6200	12000	15000	0.0800
6907 -2RS	61907 -2RS	35	55	10	9560	6200	7500	-	0.0800
6908	61908	40	62	12	13800	9300	11000	13000	0.1100
6908-ZZ	61908-ZZ	40	62	12	13800	9300	11000	13000	0.1100
6908-2RS	61908-2RS	40	62	12	13800	9300	6700	-	0.1100
6909	61909	45	68	12	10100	6700	9800	12000	0.1400
6909-ZZ	61909-ZZ	45	68	12	10100	6700	9800	12000	0.1400
6909-2RS	61909-2RS	45	68	12	10100	6700	6000	-	0.1400
6910	61910	50	72	12	14600	10400	8900	11000	0.1400
6910-ZZ	61910-ZZ	50	72	12	14600	10400	8900	11000	0.1400
6910-2RS	61910-2RS	50	72	12	14600	10400	5600	-	0.1400
6911	61911	55	80	13	15900	11400	8200	9600	0.1900
6911-ZZ	61911-ZZ	55	80	13	15900	11400	8200	9600	0.1900
6911-2RS	61911-2RS	55	80	13	15900	11400	5000	-	0.1900
6912	61912	60	85	13	16500	12000	7600	8900	0.2000
6912-ZZ	61912-ZZ	60	85	13	16500	12000	7600	8900	0.2000
6912-2RS	61912-2RS	60	85	13	16500	12000	4500	-	0.2000
6913	61913	65	90	13	17400	13400	7000	8200	0.2200
6913-ZZ	61913-ZZ	65	90	13	17400	13400	7000	8200	0.2200
6913-2RS	61913-2RS	65	90	13	17400	13400	4300	-	0.2200
6914	61914	70	100	16	23800	18300	6500	7700	0.3500
6914-ZZ	61914-ZZ	70	100	16	23800	18300	6500	7700	0.3500
6914-2RS	61914-2RS	70	100	16	23800	18300	4000	-	0.3500
6915	61915	75	105	16	24200	19300	6100	7200	0.3700
6915-ZZ	61915-ZZ	75	105	16	24200	19300	6100	7200	0.3700
6915-2RS	61915-2RS	75	105	16	24200	19300	3600	-	0.3700
6916	61916	80	110	16	25100	20400	5700	6700	0.4000
6916-ZZ	61916-ZZ	80	110	16	25100	20400	5700	6700	0.4000
6916-2RS	61916-2RS	80	110	16	25100	20400	3400	-	0.4000
6917	61917	85	120	18	32000	29600	5400	6300	0.5170
6917-ZZ	61917-ZZ	85	120	18	32000	29600	5400	6300	0.5170
6917-2RS	61917-2RS	85	120	18	32000	29600	2800	-	0.5170
6918	61918	90	125	18	33000	31500	5100	6000	0.5900

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
6918-ZZ	61918-ZZ	90	125	18	33000	31500	5100	6000	0.5900
6918-2RS	61918-2RS	90	125	18	33000	31500	2400	-	0.5900
6919	61919	95	130	18	33500	33500	4800	5700	0.6800
6919-ZZ	61919-ZZ	95	130	18	33500	33500	4800	5700	0.6800
6919-2RS	61919-2RS	95	130	18	33500	33500	3000	-	0.6800
6920	61920	100	140	20	42300	41500	4500	5300	0.8300
6920-ZZ	61920-ZZ	100	140	20	42300	41500	4500	5300	0.8300
6920-2RS	61920-2RS	100	140	20	42300	41500	4500	-	0.8300
6922	61922	110	150	20	43600	44500	4100	4800	0.9000
6922-ZZ	61922-ZZ	110	150	20	43600	44500	4100	4800	0.9000
6922-2RS	61922-2RS	110	150	20	43600	44500	4100	-	0.9000
6924	61924	120	165	22	53000	57000	3800	4400	1.2000
6924-ZZ	61924-ZZ	120	165	22	53000	57000	3800	4400	1.1290
6924-2RS	61924-2RS	120	165	22	53000	57000	3800	-	1.1290
6926	61926	130	180	24	65000	67000	3500	4100	1.6000
6926-ZZ	61926-ZZ	130	180	24	65000	67000	3500	4100	1.7800
6926-2RS	61926-2RS	130	180	24	65000	67000	3500	-	1.7800
6928	61928	140	190	24	66300	71000	3200	3800	1.7000
6928-ZZ	61928-ZZ	140	190	24	66300	71000	3200	3800	1.9000
6928-2RS	61928-2RS	140	190	24	66300	71000	3200	-	1.9000
6930	61930	150	210	28	85000	90500	3000	3500	2.4700
6930-ZZ	61930-ZZ	150	210	28	85000	90500	3000	3500	2.6400
6930-2RS	61930-2RS	150	210	28	85000	90500	3000	-	2.6400
6932	61932	160	220	28	87000	96000	2800	3300	2.6100
6932-2RS	61932-2RS	160	220	28	87000	96000	2800	-	2.6100
6934	61934	170	230	28	86000	95500	2600	3100	2.7400
6934-2RS	61934-2RS	170	230	28	86000	95500	2600	-	2.7400
6936	61936	180	250	33	110000	119000	2400	2900	4.7600
6936-2RS	61936-2RS	180	250	33	110000	119000	2400	-	4.7600
6938	61938	180	250	33	112000	132000	2300	-	5.6500
6940	61940	200	280	38	148000	166000	2200	2600	7.4000
6940-2RS	61940-2RS	200	280	38	148000	166000	2200	-	7.4000
6944	61944	220	300	38	151000	180000	2000	2300	8.0000
6948	61948	240	320	38	170000	203000	1800	2100	8.2800
6952	61952	260	360	46	212000	270000	1600	1900	14.5000
6956	61956	280	380	46	216000	285000	1500	1800	15.5000
6960	61960	300	420	56	276000	375000	1400	1600	23.5000
6964	61964	320	440	56	285000	405000	1300	1500	24.8000
6968	619618	340	460	56	293000	430000	1200	1400	26.2000
6972	61972	360	480	56	300000	455000	1100	1300	27.5000

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
60/22		22	44	12	9400	5050	17000	20000	0.0740
60/22-2RS		22	44	12	9400	5050	10000	-	0.0740
62/22		22	50	14	12900	6800	14000	17000	0.1170
62/22-2RS		22	50	14	12900	6800	9700	-	0.1170
63/22		22	56	16	18400	9250	13000	15000	0.1760
63/22-2RS		22	56	16	18400	9250	9200	-	0.1760
60/32		32	58	13	11800	8050	12000	15000	0.1290
60/32-2RS		32	58	13	11800	8050	7200	-	0.1290
62/32		32	65	17	20700	11600	15000	8700	0.2260
62/32-2RS		32	65	17	20700	11600	7100	-	0.2260
63/32		32	75	20	29800	16900	9500	11000	0.3820
63/32-2RS		32	75	20	29800	16900	6500	-	0.3820

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
98202	L15N	15	37	9	5117	2937	n/a	n/a	0.0520
98203	L17N	17	40	9	5918	3426	n/a	n/a	0.0480
98204	L20N	20	42	9	6630	3960	n/a	n/a	0.0510
98205	L25N	25	52	9	8944	5607	n/a	n/a	0.0780
98206	L30N	30	62	10	7342	5295	n/a	n/a	0.1200
98207	L35N	35	70	10	12192	8499	n/a	n/a	0.2500
98208	L40N	40	80	11	16954	12282	n/a	n/a	0.2820
98209	L45N	45	85	11	9701	7921	n/a	n/a	0.3180
98210	L50N	50	90	11	13972	11570	n/a	n/a	0.3400
98301	M12N	12	37	9	5651	3426	n/a	n/a	0.0500
98302	M15N	15	40	9	5696	3382	n/a	n/a	0.0636
98304	M20N	20	52	10	9923	6942	n/a	n/a	0.1136

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
87008	38KVLL2	8	24	10.32/8	3320	1430	23000	-	0.0200
87016	202KLL3	16	35	12.2/11	7610	3750	13000	-	0.0470
87500	200FSF	10	30	12.7/9	5070	2400	17000	-	0.0350
87501	201FSF	12	32	12.7/10	8190	3650	15000	-	0.0410
87502	202FSF	15	35	12.7/12.2	7610	3750	13000	-	0.0500
87503	202FSF	17	40	14.3/12	9560	4800	12000	-	0.0750
87504	204FSF	20	47	15.9/14	13000	6700	10000	-	0.1100
87505	205FSF	25	52	15.9/15	14000	8000	8500	-	0.1300

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
88501	201FFS/201KLL2	12	32	15.4/10	6760	3050	15000	-	0.0430
88502	202FFS/202KLL2	15	35	14.4/11	7610	3750	13000	-	0.0580
88503	203FFS/203KLL2	17	40	16.6/12	9560	4800	12000	-	0.0820
88504	204FFS/204KLL2	20	47	17.8/14	13000	6700	1000	-	0.1200
88505	205FFS/205KLL2	25	52	16.8/15	14000	8000	8500	-	0.1380
88506	206FFS/206KLL	30	62	24/16	19500	11400	7500	-	0.2600
88507	207FFS/207KLL	35	72	25/17	25500	15300	6300	-	0.3600
88508	208FFS	40	80	27/21	29100	18000	5600	-	0.4800
88509		45	85	27/21	32693	20461	5200		0.5500
88510		50	90	30/22	35139	23130	4700		0.6250