


EJ / Ejl Series Steel/Steel Maintenance Required Female Rod Ends



Bearing No.	Dimensions(mm)													Ball Diameter	a° angle	Load ratings (KN)		Weight (kg)
	d	B	C1	d2	d3-6H	h1	L3	(L4)	L5	L7	d4	d5	w			Dynamic	Static	
EJ6	6	6	4.5	21	M6	30	11	40.5	5	11.5	11	13	11	10	13	3.4	8.1	0.021
EJ8	8	8	6.5	24	M8	36	15	48	5	13	13	16	13	13	15	5.5	12.9	0.039
EJ10	10	9	7.5	29	M10	43	20	57.5	6.5	15	16	19	16	16	12	8.1	17.6	0.061
EJ12	12	10	8.5	34	M12	50	22	67	7	18	18	22	19	18	10	10	24.5	0.096
EJ15	15	12	10.5	40	M14	61	30	81	8	21	21	26	21	22	8	16	36	0.162
EJ17*	17	14	11.5	46	M16	67	32	90	10	23	25	29	27	25	10	21	45	0.233
EJ20	20	16	13.5	53	M20X1.5	77	38	103.5	10	25.5	28	34	30	29	9	30	60	0.324
EJ20-2RS*	20	16	13.5	53	M20X1.5	77	38	103.5	10	25.5	28	34	30	29	9	30	60	0.324
EJ25	25	20	18	64	M24x2	94	45	126	12	33	35	42	36	35.5	7	48	83	0.625
EJ25-2RS*	25	20	18	64	M24x2	94	45	126	12	33	35	42	36	35.5	7	48	83	0.625
EJ30	30	22	20	73	M30x2	110	54	146.5	15	37.5	42	50	46	40.7	6	62	110	0.976
EJ30-2RS*	30	22	20	73	M30x2	110	54	146.5	15	37.5	42	50	46	40.7	6	62	110	0.976
EJ35-2RS*	35	25	22	82	M36x3	125	60	166	15	40	48	58	55	47	6	79	146	1.520
EJ40-2RS*	40	28	24	92	M39x3	142	65	188	18	47	52	65	60	53	7	99	180	2.060
EJ45-2RS*	45	32	28	102	M42x3	145	65	196	20	52	58	70	65	60	7	127	240	2.720
EJ50-2RS*	50	35	31	112	M45x3	160	68	216	20	57	62	75	70	66	6	156	290	3.570
EJ60-2RS	60	44	39	135	M52x3	175	70	242.5	20	68.5	70	88	80	80	6	245	450	5.630

Right Hand Thread, *Left Hand Thread -2RS available on these size, ie. EJL17-2RS, EJL25-2RS

Bearing: 100Cr6 Bearing Steel, Hardened and Phosphated, sliding surface treated with MoS2

Body: Carbon Steel, Zinc plated

Contact surfaces: Steel/Steel - Lubrication required

**MIDLAND
BEARINGS**

Midland Bearings Ltd, Unit 33, Second Avenue, Pensnett Trading Estate, Kingswinford, West Midlands, DY6 7UG England
Tel : (0)1384-841400 Fax: (0)1384-841450 sales@midlandbearings.com