





FPL200SSN

SQUARE FLANGED THERMOPLASTIC UNITS



Part Number	Dimensions (mm / in.)										Max.Torque		Bearing Insert	Housing	Weight (kg)
	d	a	e	g	l	s	z	i	B	n	Bolt D	Nm			
FPL201SSN	12	86.0	63.5	13.4	27.8	11.0	36.3	18.0	31.0	12.7	M10	18	SS-UC201	FPL204	0.29
FPL201-8SSN	1/2	2-33/64	17/32	1-3/32	7/16	1-7/16	45/64	1.2205	0.500	0.500	3/8	18	SS-UC201-8	FPL204	0.29
FPL202SSN	15	86.0	63.5	13.4	27.8	11.0	36.3	18.0	31.0	12.7	M10	18	SS-UC202	FPL204	0.29
FPL203SSN	17	86.0	63.5	13.4	27.8	11.0	36.3	18.0	31.0	12.7	M10	18	SS-UC203	FPL204	0.29
FPL204SSN	20	86.0	63.5	13.4	27.8	11.0	36.3	18.0	31.0	12.7	M10	18	SS-UC204	FPL204	0.29
FPL204-12SSN	3/4"	3-3/8	2-33/64	17/32	1-3/32	7/16	1-7/16	45/64	1.221	0.500	3/8	18	SS-UC204-12	FPL204	0.29
FPL205SSN	25	95.0	70.0	14.3	28.0	11.0	36.7	17.0	34.1	14.3	M10	25	SS-UC205	FPL205	0.36
FPL205-16SSN	1"	3-3/4	2-3/4	9/16	1-3/32	7/16	1-7/16	43/64	1.343	0.563	3/8	25	SS-UC205-16	FPL205	0.36
FPL206SSN	30	107.0	83.0	14.3	31.5	11.0	41.4	19.2	38.1	15.9	M10	30	SS-UC206	FPL206	0.50
FPL206-20SSN	1-1/4"	4-7/32	3-17/64	9/16	1-15/64	7/16	1-5/8	3/4	1.500	0.626	3/8	30	SS-UC206-20	FPL206	0.50
FPL207SSN	35	118.0	92.0	15.5	34.8	13.0	46.9	21.5	42.9	17.5	M12	35	SS-UC207	FPL207	0.74
FPL207-20SSN	1-1/4"	4-21/32	3-5/8	39/64	1-3/8	33/64	1-27/32	27/32	1.689	0.689	7/16	35	SS-UC207-20	FPL207	0.74
FPL208SSN	40	130.0	102.0	17.0	37.5	14.0	53.2	23.0	49.2	19.0	M12	40	SS-UC208	FPL208	0.97
FPL208-24SSN	1-1/2"	5-1/8	4-1/64	43/64	1-15/32	35/64	2-3/32	29/32	1.937	0.748	7/16	40	SS-UC208-24	FPL208	0.97
FPL209SSN	45	137.0	105.0	19.0	41.0	17.0	54.2	24.0	49.2	19.0	M16	45	SS-UC209	FPL209	1.10
FPL210SSN	50	143.0	111.0	21.0	43.0	17.0	57.6	25.0	51.6	19.0	M16	50	SS-UC210	FPL210	1.25
FPL210-32SSN	2"	5-5/8	4-3/8	53/64	1-11/16	43/64	2-17/64	63/64	2.032	0.748	5/8	50	SS-UC210-32	FPL210	1.25
FPL211SSN	55	162.0	130.0	20.0	43.0	19.0	58.4	25.0	55.6	22.2	M16	55	SS-UC211	FPL211	1.40
FPL211-32SSN	2"	6-3/8	5-1/8	25/32	1-11/16	3/4	2-19/64	63/64	2.189	0.874	5/8	55	SS-UC211-32	FPL211	1.40
FPL212SSN	60	175.0	143.0	20.0	48.0	19.0	68.7	29.0	65.1	25.4	M16	60	SS-UC212	FPL212	1.60

Thermoplastic Housings are made in a High-grade glass-filled thermoplastic polyester, which has a high tensile strength and can operate in temperatures to 102°C

Colours: Sizes up to 40mm (1.1/2") are available in Black, Blue, Green and White, while sizes over 40mm (1.1/2") are only available in Black or Green

*End Caps matching the colours stated above are available to order, open design caps are only available in Green or White up to 40mm

Other bearing inserts designs will also fit in these housings, see for example: SS-SA204 to SS-SA212 / SS-SB204 to SS-SB212 / SS-UCX05 TO SS-UCX11