



STAINLESS STEEL RADIAL BALL BEARINGS

SS6200 SERIES



Part Number	Bore Diameter mm	Outer Diameter mm	Width mm	Dynamic Load Rating C (N)	Static Load Rating C0 (N)	Limiting Speed Grease r/min	Weight kg
SS6200-2RS	10	30	9	3800	2300	17000	0.032
SS6200-ZZ	10	30	9	3800	2300	25000	0.032
SS6201-2RS	12	32	10	5200	3000	15000	0.037
SS6201-ZZ	12	32	10	5200	3000	22000	0.037
SS6202-2RS	15	35	11	5900	3700	13000	0.045
SS6202-ZZ	15	35	11	5900	3700	19000	0.045
SS6203-2RS	17	40	12	7200	4700	12000	0.068
SS6203-ZZ	17	40	12	7200	4700	18000	0.068
SS6204-2RS	20	47	14	9500	6400	10000	0.106
SS6204-ZZ	20	47	14	9500	6400	16000	0.106
SS6205-2RS	25	52	15	10500	7600	8500	0.128
SS6205-ZZ	25	52	15	10500	7600	13000	0.128
SS6206-2RS	30	62	16	14600	11000	7500	0.200
SS6206-ZZ	30	62	16	14600	11000	11000	0.200
SS6207-2RS	35	72	17	19100	15000	6300	0.290
SS6207-ZZ	35	72	17	19100	15000	9800	0.290
SS6208-2RS	40	80	18	23000	18600	5600	0.370
SS6208-ZZ	40	80	18	23000	18600	8700	0.370
SS6209-2RS	45	85	19	24900	21200	5000	0.400
SS6209-ZZ	45	85	19	24900	21200	7800	0.400
SS6210-2RS	50	90	20	26300	22700	4800	0.450
SS6210-ZZ	50	90	20	26300	22700	7100	0.450
SS6211-2RS	55	100	21	32700	28400	4300	0.600
SS6211-ZZ	55	100	21	32700	28400	6400	0.600
SS6212-2RS	60	110	22	35600	31900	3700	0.780
SS6212-ZZ	60	110	22	35600	31900	6000	0.780
SS6213-2RS	65	120	23	41900	39700	3500	0.980
SS6214-2RS	70	125	24	45400	44100	3300	0.790
SS6215-2RS	75	130	25	49700	48000	3100	1.200
SS6216-2RS	80	140	26	52700	53900	2900	1.400
SS6217-2RS	85	150	28	62400	62700	2700	1.860
SS6218-2RS	90	160	30	71700	72000	2600	2.150