





# TRA Series Imperial Thrust Needle Roller Bearing Washers



| Shaft Diameter<br>(inch) | Bearing Thrust<br>Washer Part Number | d<br>mm<br>in                   | D<br>mm<br>in        | W<br>mm<br>in | Weight<br>(kg) |
|--------------------------|--------------------------------------|---------------------------------|----------------------|---------------|----------------|
| 1/4                      | TRA411                               | 6.35 <sup>+0.050/+0.300</sup>   | 17.45 -0.025/-0.760  | 0.76          | 0.001          |
|                          |                                      | 0.250 <sup>+0.002/+0.012</sup>  | 0.687 -0.010/-0.030  | 0.03          |                |
| 5/16                     | TRA512                               | 7.92 <sup>+0.050/+0.300</sup>   | 19.05 -0.025/-0.760  | 0.76          | 0.001          |
|                          |                                      | 0.312 <sup>+0.002/+0.012</sup>  | 0.750 -0.010/-0.030  | 0.03          |                |
| 3/8                      | TRA613                               | 9.53 <sup>+0.050/+0.300</sup>   | 20.625 -0.025/-0.760 | 0.76          | 0.001          |
|                          |                                      | 0.375 <sup>+0.002/+0.012</sup>  | 0.812 -0.010/-0.030  | 0.03          |                |
| 1/2                      | TRA815                               | 12.7 <sup>+0.050/+0.300</sup>   | 23.8 -0.025/-0.760   | 0.76          | 0.002          |
|                          |                                      | 0.500 <sup>+0.002/+0.012</sup>  | 0.937 -0.010/-0.030  | 0.03          |                |
| 9/16                     | TRA916                               | 14.275 <sup>+0.050/+0.300</sup> | 25.4 -0.025/-0.760   | 0.76          | 0.002          |
|                          |                                      | 0.562 <sup>+0.002/+0.012</sup>  | 1.000 -0.010/-0.030  | 0.03          |                |
| 5/8                      | TRA1018                              | 15.88 <sup>+0.050/+0.300</sup>  | 28.575 -0.025/-0.760 | 0.76          | 0.003          |
|                          |                                      | 0.625 <sup>+0.002/+0.012</sup>  | 1.125 -0.010/-0.030  | 0.03          |                |
| 3/4                      | TRA1220                              | 19.05 <sup>+0.050/+0.300</sup>  | 31.75 -0.025/-0.760  | 0.76          | 0.003          |
|                          |                                      | 0.750 <sup>+0.002/+0.012</sup>  | 1.250 -0.010/-0.030  | 0.03          |                |
| 7/8                      | TRA1423                              | 22.23 <sup>+0.050/+0.300</sup>  | 36.5 -0.025/-0.760   | 0.76          | 0.004          |
|                          |                                      | 0.875 <sup>+0.002/+0.012</sup>  | 1.437 -0.010/-0.030  | 0.03          |                |
| 7/8                      | TRA1427                              | 22.23 <sup>+0.050/+0.300</sup>  | 42.85 -0.025/-0.760  | 0.76          | 0.007          |
|                          |                                      | 0.875 <sup>+0.002/+0.012</sup>  | 1.687 -0.010/-0.030  | 0.03          |                |
| 1                        | TRA1625                              | 25.4 <sup>+0.050/+0.300</sup>   | 39.675 -0.025/-0.760 | 0.76          | 0.005          |
|                          |                                      | 1.000 <sup>+0.002/+0.012</sup>  | 1.562 -0.010/-0.030  | 0.03          |                |
| 1.1/8                    | TRA1828                              | 28.58 <sup>+0.050/+0.300</sup>  | 44.45 -0.025/-0.760  | 0.76          | 0.006          |
|                          |                                      | 1.125 <sup>+0.002/+0.012</sup>  | 1.750 -0.010/-0.030  | 0.03          |                |
| 1.1/4                    | TRA2031                              | 31.75 <sup>+0.050/+0.300</sup>  | 49.2 -0.025/-0.760   | 0.76          | 0.007          |
|                          |                                      | 1.250 <sup>+0.002/+0.012</sup>  | 1.937 -0.010/-0.030  | 0.03          |                |
| 1.3/8                    | TRA2233                              | 34.93 <sup>+0.050/+0.300</sup>  | 52.375 -0.025/-0.760 | 0.76          | 0.007          |
|                          |                                      | 1.375 <sup>+0.002/+0.012</sup>  | 2.062 -0.010/-0.030  | 0.03          |                |
| 1.1/2                    | TRA2435                              | 38.1 <sup>+0.050/+0.300</sup>   | 55.55 -0.025/-0.760  | 0.76          | 0.008          |
|                          |                                      | 1.500 <sup>+0.002/+0.012</sup>  | 2.187 -0.010/-0.030  | 0.03          |                |




# TRA Series Imperial Thrust Needle Roller Bearing Washers



| Shaft Diameter<br>(inch) | Bearing Thrust<br>Washer Part Number | d<br>mm<br>in                   | D<br>mm<br>in        | W<br>mm<br>in | Weight (kg) |
|--------------------------|--------------------------------------|---------------------------------|----------------------|---------------|-------------|
| 1.3/4                    | TRA2840                              | 44.45 <sup>+0.050/+0.300</sup>  | 63.5 -0.025/-0.760   | 0.76          | 0.010       |
|                          |                                      | 1.750 <sup>+0.002/+0.012</sup>  | 2.500 -0.010/-0.030  | 0.03          |             |
| 2                        | TRA3244                              | 50.8 <sup>+0.050/+0.300</sup>   | 69.85 -0.025/-0.760  | 0.76          | 0.011       |
|                          |                                      | 2.000 <sup>+0.002/+0.012</sup>  | 2.750 -0.010/-0.030  | 0.03          |             |
| 2.1/8                    | TRA3466                              | 53.98 <sup>+0.050/+0.300</sup>  | 73.025 -0.025/-0.760 | 0.76          | 0.012       |
|                          |                                      | 2.125 <sup>+0.002/+0.012</sup>  | 2.875 -0.010/-0.030  | 0.03          |             |
| 2.1/4                    | TRA3648                              | 57.15 <sup>+0.050/+0.300</sup>  | 76.2 -0.025/-0.760   | 0.76          | 0.012       |
|                          |                                      | 2.250 <sup>+0.002/+0.012</sup>  | 3.000 -0.010/-0.030  | 0.03          |             |
| 2.1/2                    | TRA4052                              | 63.5 <sup>+0.050/+0.430</sup>   | 82.55 -0.025/-0.760  | 0.76          | 0.013       |
|                          |                                      | 2.500 <sup>+0.002/+0.017</sup>  | 3.250 -0.010/-0.030  | 0.03          |             |
| 2.3/4                    | TRA4458                              | 69.85 <sup>+0.050/+0.430</sup>  | 92.075 -0.025/-0.760 | 0.76          | 0.018       |
|                          |                                      | 2.750 <sup>+0.002/+0.017</sup>  | 3.625 -0.010/-0.030  | 0.03          |             |
| 3                        | TRA4860                              | 76.2 <sup>+0.050/+0.430</sup>   | 95.25 -0.025/-0.760  | 0.76          | 0.015       |
|                          |                                      | 3.000 <sup>+0.002/+0.017</sup>  | 3.750 -0.010/-0.030  | 0.03          |             |
| 3.1/4                    | TRA5266                              | 82.55 <sup>+0.050/+0.430</sup>  | 104.78 -0.025/-0.760 | 0.76          | 0.020       |
|                          |                                      | 3.250 <sup>+0.002/+0.017</sup>  | 4.125 -0.010/-0.030  | 0.03          |             |
| 3.3/4                    | TRA6074                              | 95.25 <sup>+0.050/+0.430</sup>  | 117.48 -0.025/-0.760 | 0.76          | 0.023       |
|                          |                                      | 3.750 <sup>+0.002/+0.017</sup>  | 4.625 -0.010/-0.030  | 0.03          |             |
| 4.1/8                    | TRA6681                              | 104.78 <sup>+0.050/+0.430</sup> | 128.57 -0.025/-0.760 | 0.76          | 0.027       |
|                          |                                      | 4.125 <sup>+0.002/+0.017</sup>  | 5.062 -0.010/-0.030  | 0.03          |             |




# TRB Series Imperial Thrust Needle Roller Bearing Washers



| Shaft Diameter<br>(inch) | Bearing Part Number | d<br>mm<br>in                   | D<br>mm<br>in                   | W<br>mm<br>in | Weight (kg) |
|--------------------------|---------------------|---------------------------------|---------------------------------|---------------|-------------|
| 1/4                      | TRB411              | 6.35 <sup>+0.050/+0.300</sup>   | 17.45 <sup>-0.025/-0.760</sup>  | 1.52          | 0.002       |
|                          |                     | 0.250 <sup>+0.002/+0.012</sup>  | 0.687 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 5/16                     | TRB512              | 7.92 <sup>+0.050/+0.300</sup>   | 19.05 <sup>-0.025/-0.760</sup>  | 1.52          | 0.003       |
|                          |                     | 0.312 <sup>+0.002/+0.012</sup>  | 0.750 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 3/8                      | TRB613              | 9.53 <sup>+0.050/+0.300</sup>   | 20.625 <sup>-0.025/-0.760</sup> | 1.52          | 0.003       |
|                          |                     | 0.375 <sup>+0.002/+0.012</sup>  | 0.812 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 1/2                      | TRB815              | 12.7 <sup>+0.050/+0.300</sup>   | 23.8 <sup>-0.025/-0.760</sup>   | 1.52          | 0.004       |
|                          |                     | 0.500 <sup>+0.002/+0.012</sup>  | 0.937 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 9/16                     | TRB916              | 14.275 <sup>+0.050/+0.300</sup> | 25.4 <sup>-0.025/-0.760</sup>   | 1.52          | 0.004       |
|                          |                     | 0.562 <sup>+0.002/+0.012</sup>  | 1.000 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 5/8                      | TRB1018             | 15.88 <sup>+0.050/+0.300</sup>  | 28.575 <sup>-0.025/-0.760</sup> | 1.52          | 0.005       |
|                          |                     | 0.625 <sup>+0.002/+0.012</sup>  | 1.125 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 3/4                      | TRB1220             | 19.05 <sup>+0.050/+0.300</sup>  | 31.75 <sup>-0.025/-0.760</sup>  | 1.52          | 0.006       |
|                          |                     | 0.750 <sup>+0.002/+0.012</sup>  | 1.250 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 7/8                      | TRB1423             | 22.23 <sup>+0.050/+0.300</sup>  | 36.5 <sup>-0.025/-0.760</sup>   | 1.52          | 0.008       |
|                          |                     | 0.875 <sup>+0.002/+0.012</sup>  | 1.437 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 7/8                      | TRB1427             | 22.23 <sup>+0.050/+0.300</sup>  | 42.85 <sup>-0.025/-0.760</sup>  | 1.52          | 0.013       |
|                          |                     | 0.875 <sup>+0.002/+0.012</sup>  | 1.687 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 1                        | TRB1625             | 25.4 <sup>+0.050/+0.300</sup>   | 39.675 <sup>-0.025/-0.760</sup> | 1.52          | 0.009       |
|                          |                     | 1.000 <sup>+0.002/+0.012</sup>  | 1.562 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 1.1/8                    | TRB1828             | 28.58 <sup>+0.050/+0.300</sup>  | 44.45 <sup>-0.025/-0.760</sup>  | 1.52          | 0.011       |
|                          |                     | 1.125 <sup>+0.002/+0.012</sup>  | 1.750 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 1.1/4                    | TRB2031             | 31.75 <sup>+0.050/+0.300</sup>  | 49.2 <sup>-0.025/-0.760</sup>   | 1.52          | 0.014       |
|                          |                     | 1.250 <sup>+0.002/+0.012</sup>  | 1.937 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 1.3/8                    | TRB2233             | 34.93 <sup>+0.050/+0.300</sup>  | 52.375 <sup>-0.025/-0.760</sup> | 1.52          | 0.015       |
|                          |                     | 1.375 <sup>+0.002/+0.012</sup>  | 2.062 <sup>-0.010/-0.030</sup>  | 0.06          |             |
| 1.1/2                    | TRB2435             | 38.1 <sup>+0.050/+0.300</sup>   | 55.55 <sup>-0.025/-0.760</sup>  | 1.52          | 0.015       |
|                          |                     | 1.500 <sup>+0.002/+0.012</sup>  | 2.187 <sup>-0.010/-0.030</sup>  | 0.06          |             |




# TRB Series Imperial Thrust Needle Roller Bearing Washers



| Shaft Diameter<br>(inch) | Bearing Part Number | d<br>mm<br>in                   | D<br>mm<br>in        | W<br>mm<br>in | Weight (kg) |
|--------------------------|---------------------|---------------------------------|----------------------|---------------|-------------|
| 1.3/4                    | TRB2840             | 44.45 <sup>+0.050/+0.300</sup>  | 63.5 -0.025/-0.760   | 1.52          | 0.020       |
|                          |                     | 1.750 <sup>+0.002/+0.012</sup>  | 2.500 -0.010/-0.030  | 0.06          |             |
| 2                        | TRB3244             | 50.8 <sup>+0.050/+0.300</sup>   | 69.85 -0.025/-0.760  | 1.52          | 0.022       |
|                          |                     | 2.000 <sup>+0.002/+0.012</sup>  | 2.750 -0.010/-0.030  | 0.06          |             |
| 2.1/8                    | TRB3466             | 53.98 <sup>+0.050/+0.300</sup>  | 73.025 -0.025/-0.760 | 1.52          | 0.024       |
|                          |                     | 2.125 <sup>+0.002/+0.012</sup>  | 2.875 -0.010/-0.030  | 0.06          |             |
| 2.1/4                    | TRB3648             | 57.15 <sup>+0.050/+0.300</sup>  | 76.2 -0.025/-0.760   | 1.52          | 0.022       |
|                          |                     | 2.250 <sup>+0.002/+0.012</sup>  | 3.000 -0.010/-0.030  | 0.06          |             |
| 2.1/2                    | TRB4052             | 63.5 <sup>+0.050/+0.430</sup>   | 82.55 -0.025/-0.760  | 1.52          | 0.027       |
|                          |                     | 2.500 <sup>+0.002/+0.017</sup>  | 3.250 -0.010/-0.030  | 0.06          |             |
| 2.3/4                    | TRB4458             | 69.85 <sup>+0.050/+0.430</sup>  | 92.075 -0.025/-0.760 | 1.52          | 0.035       |
|                          |                     | 2.750 <sup>+0.002/+0.017</sup>  | 3.625 -0.010/-0.030  | 0.06          |             |
| 3                        | TRB4860             | 76.2 <sup>+0.050/+0.430</sup>   | 95.25 -0.025/-0.760  | 1.52          | 0.032       |
|                          |                     | 3.000 <sup>+0.002/+0.017</sup>  | 3.750 -0.010/-0.030  | 0.06          |             |
| 3.1/4                    | TRB5266             | 82.55 <sup>+0.050/+0.430</sup>  | 104.78 -0.025/-0.760 | 1.52          | -           |
|                          |                     | 3.250 <sup>+0.002/+0.017</sup>  | 4.125 -0.010/-0.030  | 0.06          |             |
| 3.3/4                    | TRB6074             | 95.25 <sup>+0.050/+0.430</sup>  | 117.48 -0.025/-0.760 | 1.52          | -           |
|                          |                     | 3.750 <sup>+0.002/+0.017</sup>  | 4.625 -0.010/-0.030  | 0.06          |             |
| 4.1/8                    | TRB6681             | 104.78 <sup>+0.050/+0.430</sup> | 128.57 -0.025/-0.760 | 1.52          | -           |
|                          |                     | 4.125 <sup>+0.002/+0.017</sup>  | 5.062 -0.010/-0.030  | 0.06          |             |




# TRC Series Imperial Thrust Needle Roller Bearing Washers



| Shaft Diameter<br>(inch) | Bearing Part Number | d<br>mm<br>in                   | D<br>mm<br>in                   | W<br>mm<br>in | Weight (kg) |
|--------------------------|---------------------|---------------------------------|---------------------------------|---------------|-------------|
| 1/4                      | TRC411              | 6.35 <sup>+0.050/+0.300</sup>   | 17.45 <sup>-0.025/-0.760</sup>  | 2.34          | 0.004       |
|                          |                     | 0.250 <sup>+0.002/+0.012</sup>  | 0.687 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 5/16                     | TRC512              | 7.92 <sup>+0.050/+0.300</sup>   | 19.05 <sup>-0.025/-0.760</sup>  | -             | -           |
|                          |                     | 0.312 <sup>+0.002/+0.012</sup>  | 0.750 <sup>-0.010/-0.030</sup>  | -             |             |
| 3/8                      | TRC613              | 9.53 <sup>+0.050/+0.300</sup>   | 20.625 <sup>-0.025/-0.760</sup> | 2.34          | 0.004       |
|                          |                     | 0.375 <sup>+0.002/+0.012</sup>  | 0.812 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 1/2                      | TRC815              | 12.7 <sup>+0.050/+0.300</sup>   | 23.8 <sup>-0.025/-0.760</sup>   | 2.34          | 0.005       |
|                          |                     | 0.500 <sup>+0.002/+0.012</sup>  | 0.937 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 9/16                     | TRC916              | 14.275 <sup>+0.050/+0.300</sup> | 25.4 <sup>-0.025/-0.760</sup>   | 2.34          | 0.006       |
|                          |                     | 0.562 <sup>+0.002/+0.012</sup>  | 1.000 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 5/8                      | TRC1018             | 15.88 <sup>+0.050/+0.300</sup>  | 28.575 <sup>-0.025/-0.760</sup> | 2.34          | 0.008       |
|                          |                     | 0.625 <sup>+0.002/+0.012</sup>  | 1.125 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 3/4                      | TRC1220             | 19.05 <sup>+0.050/+0.300</sup>  | 31.75 <sup>-0.025/-0.760</sup>  | 2.34          | 0.010       |
|                          |                     | 0.750 <sup>+0.002/+0.012</sup>  | 1.250 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 7/8                      | TRC1423             | 22.23 <sup>+0.050/+0.300</sup>  | 36.5 <sup>-0.025/-0.760</sup>   | 2.34          | 0.012       |
|                          |                     | 0.875 <sup>+0.002/+0.012</sup>  | 1.437 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 7/8                      | TRC1427             | 22.23 <sup>+0.050/+0.300</sup>  | 42.85 <sup>-0.025/-0.760</sup>  | 2.34          | 0.020       |
|                          |                     | 0.875 <sup>+0.002/+0.012</sup>  | 1.687 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 1                        | TRC1625             | 25.4 <sup>+0.050/+0.300</sup>   | 39.675 <sup>-0.025/-0.760</sup> | 2.34          | 0.013       |
|                          |                     | 1.000 <sup>+0.002/+0.012</sup>  | 1.562 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 1.1/8                    | TRC1828             | 28.58 <sup>+0.050/+0.300</sup>  | 44.45 <sup>-0.025/-0.760</sup>  | 2.34          | 0.017       |
|                          |                     | 1.125 <sup>+0.002/+0.012</sup>  | 1.750 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 1.1/4                    | TRC2031             | 31.75 <sup>+0.050/+0.300</sup>  | 49.2 <sup>-0.025/-0.760</sup>   | 2.34          | 0.020       |
|                          |                     | 1.250 <sup>+0.002/+0.012</sup>  | 1.937 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 1.3/8                    | TRC2233             | 34.93 <sup>+0.050/+0.300</sup>  | 52.375 <sup>-0.025/-0.760</sup> | 2.34          | 0.018       |
|                          |                     | 1.375 <sup>+0.002/+0.012</sup>  | 2.062 <sup>-0.010/-0.030</sup>  | 0.092         |             |
| 1.1/2                    | TRC2435             | 38.1 <sup>+0.050/+0.300</sup>   | 55.55 <sup>-0.025/-0.760</sup>  | 2.34          | 0.023       |
|                          |                     | 1.500 <sup>+0.002/+0.012</sup>  | 2.187 <sup>-0.010/-0.030</sup>  | 0.092         |             |



# TRC Series Imperial Thrust Needle Roller Bearing Washers



| Shaft Diameter<br>(inch) | Bearing Part Number | d<br>mm<br>in                   | D<br>mm<br>in        | W<br>mm<br>in | Weight (kg) |
|--------------------------|---------------------|---------------------------------|----------------------|---------------|-------------|
| 1.3/4                    | TRC2840             | 44.45 <sup>+0.050/+0.300</sup>  | 63.5 -0.025/-0.760   | 2.34          | 0.029       |
|                          |                     | 1.750 <sup>+0.002/+0.012</sup>  | 2.500 -0.010/-0.030  | 0.092         |             |
| 2                        | TRC3244             | 50.8 <sup>+0.050/+0.300</sup>   | 69.85 -0.025/-0.760  | 2.34          | 0.033       |
|                          |                     | 2.000 <sup>+0.002/+0.012</sup>  | 2.750 -0.010/-0.030  | 0.092         |             |
| 2.1/8                    | TRC3466             | 53.98 <sup>+0.050/+0.300</sup>  | 73.025 -0.025/-0.760 | 2.34          | 0.035       |
|                          |                     | 2.125 <sup>+0.002/+0.012</sup>  | 2.875 -0.010/-0.030  | 0.092         |             |
| 2.1/4                    | TRC3648             | 57.15 <sup>+0.050/+0.300</sup>  | 76.2 -0.025/-0.760   | 2.34          | 0.037       |
|                          |                     | 2.250 <sup>+0.002/+0.012</sup>  | 3.000 -0.010/-0.030  | 0.092         |             |
| 2.1/2                    | TRC4052             | 63.5 <sup>+0.050/+0.430</sup>   | 82.55 -0.025/-0.760  | 2.34          | 0.041       |
|                          |                     | 2.500 <sup>+0.002/+0.017</sup>  | 3.250 -0.010/-0.030  | 0.092         |             |
| 2.3/4                    | TRC4458             | 69.85 <sup>+0.050/+0.430</sup>  | 92.075 -0.025/-0.760 | 2.34          | 0.051       |
|                          |                     | 2.750 <sup>+0.002/+0.017</sup>  | 3.625 -0.010/-0.030  | 0.092         |             |
| 3                        | TRC4860             | 76.2 <sup>+0.050/+0.430</sup>   | 95.25 -0.025/-0.760  | 2.34          | 0.061       |
|                          |                     | 3.000 <sup>+0.002/+0.017</sup>  | 3.750 -0.010/-0.030  | 0.092         |             |
| 3.1/4                    | TRC5266             | 82.55 <sup>+0.050/+0.430</sup>  | 104.78 -0.025/-0.760 | 2.34          | -           |
|                          |                     | 3.250 <sup>+0.002/+0.017</sup>  | 4.125 -0.010/-0.030  | 0.092         |             |
| 3.3/4                    | TRC6074             | 95.25 <sup>+0.050/+0.430</sup>  | 117.48 -0.025/-0.760 | 2.34          | -           |
|                          |                     | 3.750 <sup>+0.002/+0.017</sup>  | 4.625 -0.010/-0.030  | 0.092         |             |
| 4.1/8                    | TRC6681             | 104.78 <sup>+0.050/+0.430</sup> | 128.57 -0.025/-0.760 | 2.34          | -           |
|                          |                     | 4.125 <sup>+0.002/+0.017</sup>  | 5.062 -0.010/-0.030  | 0.092         |             |