



Bearing NO.	Dimensions (mm / in.)									Dynamic load ratings (N)	Static load ratings (N)	Weight (kg)
	d	D	B	C	S	S1	ds	F	G			
CSB201	12	40	22	12	6.0	16.0	M5X0.8	3.4	4.0	9600	4600	0.10
201-8*	1/2	1.5748	0.8661	0.4724	0.2362	0.6299	10-32UNF	0.1339	0.1575			0.10
CSB202	15	40	22	12	6.0	16.0	M5X0.8	3.4	4.0	9600	4600	0.10
202-9*	9/16	1.5748	0.8661	0.4724	0.2362	0.6299	10-32UNF	0.1339	0.1575			0.10
202-10	5/8											0.10
CSB203	17	40	22	12	6.0	16.0	M5X0.8	3.4	4.0	9600	4600	0.09
203-11*	11/16	1.5748	0.8661	0.4724	0.2362	0.6299	10-32UNF	0.1339	0.1575			0.09
CSB204	20	47	25	14	7.0	18.0	M6X1	4.2	4.6	12800	6600	0.13
204-12	3/4	1.8504	0.9843	0.5512	0.2756	0.7087	1/4-28UNF	0.1654	0.1811			0.14
CSB205	25	52	27	15	7.5	19.5	M6X1	4.3	5.5	14000	7850	0.16
205-13*	13/16	2.0472	1.0630	0.5906	0.2953	0.7677	1/4-28UNF	0.1693	0.2165			0.19
205-14*	7/8											0.18
205-15*	15/16											0.17
205-16	1											0.16
CSB206	30	62	30	16	8.0	22.0	M6X1	5	6	19450	11250	0.25
206-17*	1-1/16	2.4409	1.1811	0.6299	0.3150	0.8661	1/4-28UNF	0.1969	0.2362			0.28
206-18*	1-1/8											0.26
206-19*	1-3/16											0.25
206-20*	1-1/4											0.24
CSB207	35	72	32	17	8.5	23.5	M8X1	5.6	6.5	25700	15200	0.36
207-20	1-1/4	2.8346	1.2598	0.6693	0.3346	0.9252	5/16-24UNF	0.2205	0.2559			0.41
207-21*	1-5/16											0.39
207-22*	1-3/8											0.36
207-23*	1-7/16											0.35
CSB208	40	80	34	18	9.0	25.0	M8X1	5.9	7.7	29500	18100	0.45
208-24	1-1/2	3.1496	1.3386	0.7087	0.3543	0.9843	5/16-24UNF	0.2323	0.3031			0.43
208-25*	1-9/16											0.45
CSB209	45	85	41.2	19	10.2	31.0	M8X1	6.1	8.0	32700	20900	0.54
209-26*	1-5/8	3.3465	1.6220	0.7480	0.4016	1.2205	5/16-24UNF	0.2402	0.3150			
209-27*	1-11/16											
209-28*	1-3/4											
CSB210	50	90	43.5	20	10.9	32.6	M10X1	6.5	10	35000	23200	0.62

*Factory order size